


Linear Guideways

QR Series

2-10-11 Dimensions for QR series

(1) QRH-CA / QRH-HA



Model No.	Dimensions of Assembly (mm)		Dimensions of Block (mm)												Dimensions of Rail (mm)			Mounting Bolt for Rail	Basic Dynamic Load Rating	Basic Static Load Rating	Static Rated Moment			Weight							
			H	H1	N	W	B	B1	C	L1	L	K1	K2	G	Mxl	T	H2	H3	WR	HR	D	h	d	P	E	[mm]	C(kN)	C0(kN)	kN-m	kN-m	kN-m
	H	H1	N	W	B	B1	C	L1	L	K1	K2	G	Mxl	T	H2	H3	WR	HR	D	h	d	P	E	[mm]	C(kN)	C0(kN)	kN-m	kN-m	kN-m	Block kg	Rail kg/m
QRH20CA	34	5	12	44	32	6	36	57.5	86	15.8	6	5.3	M5x8	8	8.3	8.3	20	21	9.5	8.5	6	30	20	M5x20	26.3	38.9	0.591	0.453	0.453	0.40	2.66
QRH25CA	40	5.5	12.5	48	35	6.5	35	66	97.9	20.75	7.25	12	M6x8	9.5	10.2	10	23	23.6	11	9	7	30	20	M6x20	38.5	54.4	0.722	0.627	0.627	0.60	3.08
QRH25HA	40	5.5	12.5	48	35	6.5	50	81	112.9	21.5	7.25	12	M6x8	9.5	10.2	10	23	23.6	11	9	7	30	20	M6x20	44.7	65.3	0.867	0.907	0.907	0.74	3.08
QRH30CA	45	6	16	60	40	10	40	71	109.8	23.5	8	12	M8x10	9.5	9.5	10.3	28	28	14	12	9	40	20	M8x25	51.5	73.0	1.284	0.945	0.945	0.89	4.41
QRH30HA	45	6	16	60	40	10	60	93	131.8	24.5	8	12	M8x10	9.5	9.5	10.3	28	28	14	12	9	40	20	M8x25	64.7	95.8	1.685	1.63	1.63	1.15	4.41
QRH35CA	55	6.5	18	70	50	10	50	79	124	22.5	10	12	M8x12	12	16	19.6	34	30.2	14	12	9	40	20	M8x25	77.0	94.7	1.955	1.331	1.331	1.56	6.06
QRH35HA	55	6.5	18	70	50	10	72	106.5	151.5	25.25	10	12	M8x12	12	16	19.6	34	30.2	14	12	9	40	20	M8x25	95.7	126.3	2.606	2.335	2.335	2.04	6.06
QRH45CA	70	8	20.5	86	60	13	60	106	153.2	31	10	12.9	M10x17	16	20	24	45	38	20	17	14	52.5	22.5	M12x35	123.2	156.4	3.959	2.666	2.666	3.16	9.97
QRH45HA	70	8	20.5	86	60	13	80	139.8	187	37.9	10	12.9	M10x17	16	20	24	45	38	20	17	14	52.5	22.5	M12x35	150.8	208.6	5.278	4.694	4.694	4.10	9.97

Note : 1 kgf = 9.81 N