



5.4 KU Series

Model Number for KU60

KU060	-10	P	-600	A	F0	S1	M
Model	Lead	Precision Grade	Effective Stroke	Slider Type	Motor Flange	Limit Switch	Motor
	5 mm 10 mm	C: Normal P: Precision		A: Standard	F0: 100W F: Without Flange	S1: OMRON SX671 S2: OMRON SX674 S3: SUNX GX-F12A S4: SUNX GX-F12A-P None: Without Sensor	M: Supplied With Motor None: Without Motor



Effective Stroke (mm)	L1	L2	Weight (kg)	AC motor output		W	100	
				Drive			Ballscrew C7(normal)	
	50	297	331	1	Lead	mm	5	10
	100	347	381	1.5	Rated RPM	RPM	3000	3000
	150	397	431	2	Max linear speed*	mm/sec	250	500
	200	447	481	2.5	Rated thrust	N	280	140
	250	497	531	3	Repeatability	mm	±0.02	
	300	547	581	3.5	Effective stroke	mm	50~600	
	350	597	631	4	Max load (H)	kg	47	32
	400	647	681	4.5		Fyd	N	50
450	697	731	5	Fzd		N	470	320
500	747	781	5.5	Mxd		N-m	7	7
550	797	831	6	Myd		N-m	27	33
600	847	881	6.5	Mzd		N-m	2	2
				Permitted Load	$\frac{F_y}{F_{yd}} + \frac{F_z}{F_{zd}} + \frac{M_x}{M_{xd}} + \frac{M_y}{M_{yd}} + \frac{M_z}{M_{zd}} \leq 1$			
				condition***	Fy、Fz、Mx、My、Mz are working loads			

Motor Adaptor Flange F0

* Vibration might occur when the effective stroke is longer than 500mm.

The maximum speed should be decreased by 15% for every 50mm of increased stroke.

**The load condition is based on 10,000km operation

***For horizontal application only. If used in special condition, please contact HIWIN.